

**TRUCK UTILITY LT GS SERIES 3 LANDROVER, ALL TYPES
FITTING OF IMPROVED TYPE, LEFT SIDE REAR VISION MIRROR ARM
MODIFICATION INSTRUCTION**

Reference: A. AC in WM No 29055/1

Introduction

1. This instruction details the fitting of a 245 mm rear vision mirror arm to the left side of the vehicle.

General

2. **Estimated Manhours to Perform.** 0.1 (initial planning only).
3. **Priority.** Group 2.
 - a. All vehicles on issue to units are to be modified when next in workshops for repair.
 - b. All equipments held by supply depots should normally be modified before issue. Where unmodified equipments would delay priority issues, equipments may be released unmodified provided their record books are endorsed with details of outstanding modifications.
4. **Modification to be Applied to.** All subject vehicles that are fitted with a 165 mm left side rear vision mirror arm.
5. **Item Affected.** Left side rear vision mirror assembly.
6. **Action Required.** By RAEME tradesmen authorized to carry out unit, field and base repairs in accordance with WKSP A 850.

TABLE 1 — STORES REQUIRED (To be demanded through normal supply channels)

Item	DSN	Designation	Qty per Equip
1.	2540-66-106-0500	ARM, REAR VIEW, MIRROR, left hand 245 mm lg	1

TABLE 2 — STORES REMOVED (To be disposed of in accordance with GEN P series)

Item	DSN	Designation	Qty per Equip
1.	NIC	ARM, REAR VIEW, MIRROR, left hand, 165 mm lg	1

Detail

7. Modification procedure is as follows:
 - a. Remove the left side rear view mirror head from the arm.
 - b. Remove the arm from the vehicle.
 - c. If necessary straighten the mirror arm mounting bracket so that it is aligned with the one on the right side of the vehicle.
 - d. Using the original bolt nut and washer, fit the mirror arm to the mounting bracket. Ensure the arm is angled towards the rear of the vehicle.
 - e. Fit the mirror head to the arm and adjust for the correct rear view.
 - f. Ensure that when fully open, the passenger door clears the mirror head.

Modification Record Plate

8. Deface the numeral 3 on the modification record plate situated on the side of the front passenger seat base, adjacent to the vehicle specification plate.

E N D